

## IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1           1.       (Original)     A mass storage controller system, comprising:  
2           a plurality of controllers for controlling an array of storage devices, each of the  
3 plurality of controllers comprising:  
4                 a CPU for controlling the operation of a controller;  
5                 program memory, coupled to the CPU, for storing program instructions and  
6 variables for the operation of the CPU; and  
7                 cache memory, coupled to the CPU, for storing information related to the  
8 array of storage devices;  
9           wherein a controller of the plurality of controllers initiates a task to be performed, the  
10 controller initiating the task establishes a task coordination data object shared by the plurality  
11 of controllers, wherein the task coordination data object represents discrete partitions of the  
12 task to be performed and states for each partition, and wherein a free controller of the  
13 plurality of controllers selects a partition of the task available for processing as indicated by  
14 the states.

1           2.       (Original)     (Original)     The mass storage controller system of claim 1,  
2 wherein the state indicates whether a partition is READY, IN PROGRESS, or COMPLETE.

1           3.       (Original)     (Original)     The mass storage controller system of claim 2,  
2 wherein a controller selects a partition by examining the partitions in a READY state and  
3 selecting at least one partition in the READY state to operate on.

1           4.       (Original)     (Original)     The mass storage controller system of claim 3,  
2 wherein a partition is in an IN PROGRESS state during processing.

1           5.       (Original)     (Original)     The mass storage controller system of claim 4,  
2 wherein a controller sets the partition selected for processing to a COMPLETE state upon  
3 completion of processing for a partition.

1           6.       (Original)     (Original)     The mass storage controller system of claim 1,  
2 wherein a controller selects a partition by examining the partitions in a READY state and  
3 selecting at least one partition in the READY state to operate on.

1           7.       (Original)     (Original)     The mass storage controller system of claim 1,  
2 wherein a partition is in an IN PROGRESS state during processing.

1           8.       (Original)     (Original)     The mass storage controller system of claim 1,  
2 wherein a controller sets the partition selected for processing to a COMPLETE state upon  
3 completion of processing for a partition.

1           9.       (Original)     (Original)     The mass storage controller system of claim 1,  
2 wherein the states provide a semaphore-mechanism for allowing a controller to ascertain  
3 whether to acquire control over a partition.

1           10.      (Original)     (Original)     The mass storage controller system of claim 1,  
2 wherein the initiating controller is notified when all partition states are COMPLETE and  
3 performs whatever completion actions are required.

1           11.      (Original)     (Original)     The mass storage controller system of claim 1,  
2 wherein the task coordination data object includes information about an operation to be  
3 performed and a data set to be operated on.

1           12.   (Original)   (Original)   A mass storage array subsystem, comprising:  
2           a plurality of storage devices;  
3           a backplane, coupled to the plurality of storage devices, adapted to couple to said  
4           plurality of storage devices; and  
5           a plurality of controllers, coupled to the backplane, for controlling the plurality of  
6           storage devices, the plurality of controllers having a first interface ~~to couple~~ coupled to a host  
7           system and a second interface ~~adapted to couple~~ coupled to said backplane to communicate  
8           with said plurality of storage devices;  
9           wherein each of the plurality of controllers comprise a CPU for controlling the  
10          operation of a controller, program memory for storing program instructions and variables for  
11          the operation of the CPU and cache memory for storing information related to the array of  
12          storage devices, and wherein a controller of the plurality of controllers initiates a task to be  
13          performed, the controller initiating the task establishes a task coordination data object shared  
14          by the plurality of controllers, wherein the task coordination data object represents discrete  
15          partitions of the task to be performed and states for each partition, and wherein a free  
16          controller of the plurality of controllers selects a partition of the task available for processing  
17          as indicated by the states.

1           13.   (Original)   (Original)   The mass storage array subsystem of claim 12,  
2           wherein the state indicates whether a partition is READY, IN PROGRESS, or COMPLETE.

1           14.   (Original)   (Original)   The mass storage array subsystem of claim 13,  
2           wherein a controller selects a partition by examining the partitions in a READY state and  
3           selecting at least one partition in the READY state to operate on.

1           15.   (Original)   (Original)   The mass storage array subsystem of claim 14,  
2           wherein a partition is in an IN PROGRESS state during processing.

1           16.   (Original)   (Original)   The mass storage array subsystem of claim 15,  
2           wherein a controller sets the partition selected for processing to a COMPLETE state upon  
3           completion of processing for a partition.

1           17.   (Original)   (Original)   The mass storage array subsystem of claim 12,  
2 wherein a controller selects a partition by examining the partitions in a READY state and  
3 selecting at least one partition in the READY state to operate on.

1           18.   (Original)   (Original)   The mass storage array subsystem of claim 12,  
2 wherein a partition is in an IN PROGRESS state during processing.

1           19.   (Original)   (Original)   The mass storage array subsystem of claim 12,  
2 wherein a controller sets the partition selected for processing to a COMPLETE state upon  
3 completion of processing for a partition.

1           20.   (Original)   (Original)   The mass storage array subsystem of claim 12,  
2 wherein the states provide a semaphore-mechanism for allowing a controller to ascertain  
3 whether to acquire control over a partition.

1           21.   (Original)   The mass storage array subsystem of claim 12, wherein the  
2 initiating controller is notified when all partition states are COMPLETE and performs  
3 whatever completion actions are required.

1           22.   (Original)   The mass storage array subsystem of claim 12, wherein the  
2 task coordination data object includes information about an operation to be performed and a  
3 data set to be operated on.

1           23.   (Currently Amended) A method for cooperative distributed task management  
2 in a storage subsystem with multiple controllers ~~using cache locking~~, comprising:  
3           initiating by an initiating controller a task to be performed;  
4           establishing by the initiating controller a task coordination data object shared by the  
5 multiple controllers, wherein the task coordination data object represents discrete partitions  
6 of the task to be performed and states for each partition; and           selecting by a free  
7 controller a partition of a task available for processing as indicated by the states.

1           24.    (Original)    The method of claim 23 further comprising indicating a state of  
2 a partition as being READY, IN PROGRESS, or COMPLETE.

1           25.    (Original)    The method of claim 24 wherein the selecting by a free  
2 controller is performed by examining the partitions in a READY state and selecting at least  
3 one partition in the READY state to operate on.

1           26.    (Original)    The method of claim 25, wherein a partition is in an IN  
2 PROGRESS state during processing.

1           27.    (Original)    The method of claim 26 further comprising setting by a  
2 controller a partition selected for processing to a COMPLETE state upon completion of  
3 processing for the partition.

1           28.    (Original)    The method of claim 23, wherein the selecting by a free  
2 controller is performed by examining the partitions in a READY state and selecting at least  
3 one partition in the READY state to operate on.

1           29.    (Original)    The method of claim 23, wherein a partition is in an IN  
2 PROGRESS state during processing.

1           30.    (Original)    The method of claim 23 further comprising setting by a  
2 controller a partition selected for processing to a COMPLETE state upon completion of  
3 processing for the partition.

1           31.    (Original)    The method of claim 23 wherein the states provide a  
2 semaphore-mechanism for allowing a controller to ascertain whether to acquire control over  
3 a partition.

1           32.    (Original)    The method of claim 23 further comprising notifying the  
2   initiating controller when all partition states are complete and performing completion actions  
3   that are required.

1           33.    (Original)    The method of claim 23, wherein the task coordination data  
2   object includes information about an operation to be performed and a data set to be operated  
3   on.

1           34.    (Currently Amended) An article of manufacture comprising a program  
2   storage medium readable by a computer, the medium tangibly embodying one or more  
3   programs of instructions executable by the computer to perform a method for cooperative  
4   distributed task management in a storage subsystem with multiple controllers ~~using cache~~  
5   ~~locking~~, the method comprising:  
6        initiating by an initiating controller a task to be performed;  
7        establishing by the initiating controller a task coordination data object shared by the  
8   multiple controllers, wherein the task coordination data object represents discrete partitions  
9   of the task to be performed and states for each partition; and        selecting by a free  
10   controller a partition of a task available for processing as indicated by the states.

1           35.    (Original)    The article of manufacture of claim 34 further comprising  
2   indicating a state of a partition as being READY, IN PROGRESS, or COMPLETE.

1           36.    (Original)    The article of manufacture of claim 35 wherein the selecting by  
2   a free controller is performed by examining the partitions in a READY state and selecting at  
3   least one partition in the READY state to operate on.

1           37.    (Original)    The article of manufacture of claim 36, wherein a partition is in  
2   an IN PROGRESS state during processing.

1           38.     (Original)     The article of manufacture of claim 37 further comprising  
2     setting by a controller a partition selected for processing to a COMPLETE state upon  
3     completion of processing for the partition.

1           39.     (Original)     The article of manufacture of claim 34, wherein a free  
2     controller selects a partition by examining the partitions in a READY state and selecting at  
3     least one to operate on.

1           40.     (Original)     The article of manufacture of claim 34 further comprising  
2     notifying the initiating controller is notified when all partition states are complete and  
3     performs whatever completion actions required.

1           41.     (Original)     The article of manufacture of claim 34, wherein the task  
2     coordination data object includes information about an operation to be performed and a data  
3     set to be operated on.

1           42.     (Original)     A mass storage controller system, comprising:  
2             a plurality of intermediate controller means for controlling an array of storage  
3     devices, each of the plurality of controllers comprising:  
4                 CPU means for controlling the operation of a controller;  
5                 program memory means, coupled to the CPU means, for storing program  
6     instructions and variables for the operation of the CPU; and  
7                 cache memory means, coupled to the CPU means, for storing information  
8     related to the array of storage devices;  
9             wherein an intermediate controller means of the plurality of intermediate controller  
10    means initiates a task to be performed, the intermediate controller means initiating the task  
11    establishes a task coordination data object shared by the plurality of intermediate controller  
12    means controller means, wherein the task coordination data object represents discrete  
13    partitions of the task to be performed and states for each partition, and wherein a free  
14    intermediate controller means selects a partition of the task available for processing as  
15    indicated by the states.